

Modello	POTENZA MAX KVA		MOTORE						DIMENSIONI	PESO	RUMOROSITA'
	400 v	230 v	Tipo	N. Cil.	Cilindrata cc.	Potenza Cv	Serbatoio Lt	Consumo Lt/h	L X L X A mm.	Kg.	Lwa
GP 650M/RM	/	0,55	ROBIN EY 08	1	78	2	2	0,6	370x265x345	18,5	84
GP 1300M/RM	/	1,05	ROBIN EY 15	1	143	3,5	4,1	0,9	490x288x410	27,5	87
GP 2400M/RM	/	2	ROBIN EH 17	1	172	6	5	1	550x325x450	41	89
Model	400 v	230 v	Model	N. Cyl.	Displacement cc.	Power Hp	Tank capacity Lt.	Fuel consumption Lt/h	L x W x H mm.	Kg.	Lwa
	MAX POWER KVA		ENGINE						DIMENSIONS	WEIGHT	NOISE LEVEL



Modello	POTENZA MAX KVA		MOTORE						DIMENSIONI	PESO	RUMOROSITA'
	400 v	230 v	Tipo	N. Cil.	Cilindrata cc.	Potenza Cv	Serbatoio Lt	Consumo Lt/h	L X L X A mm.	Kg.	Lwa
GP 4000SM/BE	/••	3,5	ROBIN EH 25	1	251	8,5	16,5	2,4	785x480x660	100	87
GP 4000SM/DE	/	3,1	ROBIN DY 27D	1	265	5,5	16,5	2,7	785x480x660	100	90
GP 6000SM/DE	/	5	LOMBARDINI 6 LD 435	1	436	10	20	1,9	940x540x800	173	92
GP 6000ST/DE	6	2,5	LOMBARDINI 6 LD 435	1	436	10	20	1,9	940x540x800	224	92
GP 8000SM/BE	/••	6,3	ROBIN EH 41	1	404	13,5	20	2,7	940x520x800	168	90
GP 8000ST/BE	7,0••	4,5	ROBIN EH 41	1	404	13,5	20	2,7	940x520x800	175	90
GP 12000SM/DE	/••	12,6	LOMBARDINI 12 LD 475	2	871	20	30	4	1100x540x930	300	95
GP 12000ST/DE	12*••	4	LOMBARDINI 12 LD 435	2	871	18	30	4	1100x540x930	290	95
Model	400 v	230 v	Model	N. Cyl.	Displacement cc.	Power Hp	Tank capacity Lt.	Fuel consumption Lt/h	L x W x H mm.	Kg.	Lwa
	MAX POWER KVA		ENGINE						DIMENSIONS	WEIGHT	NOISE LEVEL

Dotazione di serie Standard features / Standard Ausstattung / Équipement standard	Configurazioni diverse Other configurations / Andere Konfigurationen / Équipement différent
Interruttore magnetotermico / Magnetothermic circuit breaker Thermisch magnetischer Schutzschalter / Interrupteur magnétothermique	Versioni con tensioni differenti / Models with different voltage Modelle mit anderen Spannungen / Voltage différents
Presse 16A 230V / Socket 16A 230V Steckdose 16A 230v / Prise de 16A 230v	Versioni a 60 Hz / 60 Hz versions Stromerzeuger 60 Hz / Modèles de 60 Hz
Presse 16A 400V / Socket 16A 400V Steckdose 16A 400v / Prise de 16A 400v	Avviamento automatico / Automatic start Automatischer starter / Démarrage automatique
Contatore / Hours run meter Betriebs-Stundenzähler / Compteur horaire	
Voltmetro / Voltmeter / Voltmeter / Voltmètre	
*Frequenzmetro / *Frequency meter *Frequenzmesser / *Fréquencemètre	
••Protezione olio / Oil sensor Öldruck-Kontrolllampe / Sécurité manque d'huile	
*Protezione sovratemperatura / *Overheating protection *Kühlwasserübertemperatur / *Sécurité température élevée	

