



Modello	Potenza Continua		Tensione	Giri alternatore	Giri presa di forza	Potenza consigliata trattore	Dimensioni	Peso
	KVA	KW	V	giri/min.	giri/min.	CV.	L X L X A mm.	Kg.
GP 6,5 TR	6,5	5,2	400/230	3000	430	20	820 x 890 x 810	80
GP 10 TR	10	8	400/230	3000	430	20	820 x 890 x 810	95
GP 12,5 TR	12,5	10	400/230	3000	430	35	820 x 890 x 810	105
GP 16 TR	16	12,8	400/230	3000	430	45	820 x 890 x 810	115
GP 20 TR	20	16	400/230	3000	430	45	820 x 890 x 810	125
GP 25 TR	25	20	400/230	3000	430	55	980 X 940 X 840	165
GP 30 TR	30	25,2	400/230	3000	430	60	980 X 940 X 840	185
Model	KVA	KW	V	RPM	RPM	HP	L x W x H mm.	Kg.
	Continuous Power		Voltage	Alternator revolution	PTO revolution	Recommended tractor power	Dimensions	Weight

Dotazione di serie Standard features / Standard Ausstattung / Équipement standard	Accessori a richiesta Options on request / Zubehöre auf Anfrage / Accessoires sur demande	Configurazioni diverse Other configurations / Andere Konfigurationen / Équipement différent
Interruttore magnetotermico / Magnetohermic circuit breaker Thermisch magnetischer Schutzschalter / Interrupteur magnétothermique	Interruttore differenziale / Earth fault device Thermischer Schutzschalter / Interrupteur différentiel	Versione IP 45 / IP45 version Generator in Schutzart IP 45 / Protection IP 45
Voltmetro / Voltmeter Voltmeter / Voltmètre	Frequenzimetro / Frequency-meter Frequenzmesser / Fréquencecètre	
Presa 16A 230V / Socket 16A 230V Steckdose 16A 230v / Prise de 16A 230v	Amperometro / Ammeter Amperemeter / Ampèremètre	
Presa 16/32A 400V / Socket 16/32A 400V Steckdose 16/32A 400v / Prise de 16/32A 400v		



Modello	Potenza Continua		Tensione	Giri alternatore	Giri presa di forza	Potenza consigliata trattore	Dimensioni	Peso
	KVA	KW	V	giri/min.	giri/min.	CV.	L X L X A mm.	Kg.
GP 20 TR/S	20	16	400/230	1500	430	50	980 x 940 x 980	235
GP 30 TR/S	30	24	400/230	1500	430	70	1250 x 1050 x 1180	330
GP 40 TR/S	40	32	400/230	1500	430	85	1250 x 1050 x 1180	360
GP 60 TR/S	60	48	400/230	1500	500	120	1250 x 1050 x 1180	445
Model	KVA	KVA	V	RPM	RPM	HP	L x W x H mm.	Kg.
	Continuous Power		Voltage V	Alternator revolution	PTO revolution	Recommended tractor power	Dimensions	Weight

Dotazione di serie Standard features / Standard Ausstattung / Équipement standard	Accessori a richiesta Options on request / Zubehöre auf Anfrage / Accessoires sur demande	Configurazioni diverse Other configurations / Andere Konfigurationen / Équipement différent
Interruttore magnetotermico / Magnetohermic circuit breaker Thermisch magnetischer Schutzschalter / Interrupteur magnétothermique	Interruttore differenziale / Earth fault device Thermischer Schutzschalter / Interrupteur différentiel	Versione IP 45 / IP45 version Generator in Schutzart IP 45 / Protection IP 45
Voltmetro / Voltmeter Voltmeter / Voltmètre	Frequenzimetro / Frequency-meter Frequenzmesser / Fréquencecètre	
Presa 16A 230V / Socket 16A 230V Steckdose 16A 230v / Prise de 16A 230v	Amperometro / Ammeter Amperemeter / Ampèremètre	
Presa 16/32A 400V / Socket 16/32A 400V Steckdose 16/32A 400v / Prise de 16/32A 400v		

